




Open/Closed Bushings



A black nylon bushing for side entry and encirclement of pre-assembled harnesses, capillary tubes or other units that have sections larger than the bushing's ID. Can also be assembled into holes that already contain cable or tubing. Fingertip pressure snaps the bushing into the mounting hole, forming a complete circle and insulation barrier against the raw edge of the chassis hole.

Part No.	Mounting Hole Diameter	A Inside Diameter	B Head Diameter	C Overall Height	Max. Chassis Thickness	Minimum Order Quantity
OCB375	.375	.265	.421	.390	.125	1,000
OCB437	.437	.312	.500	.406	.125	1,000
OCB500	.500	.312	.562	.406	.125	1,000
OCB562	.562	.390	.640	.406	.125	1,000
OCB625	.625	.453	.687	.406	.125	1,000
OCB750	.750	.546	.796	.406	.125	1,000
OCB875	.875	.671	.921	.406	.125	1,000
OCB1000	1.000	.812	1.047	.406	.125	500
OCB1093	1.093	.875	1.156	.406	.125	1,000
OCB1250	1.250	1.046	1.343	.406	.125	500
OCB1375	1.375	1.171	1.468	.406	.125	500
OCB1500	1.500	1.250	1.578	.421	.125	500

Standard colour: **Black**. White and other colours available at premium charge if quantities are sufficient.