



Feet and Bumpers

SELF-ADHESIVE

With no holes to drill and no screws or rivets needed, self-adhesive bumpers will save you time and money. Kiss-cut for easy application, they simply peel off and press onto almost any smooth surface. They are non-marring, non-staining, skid and scratch resistant and they won't harden or crack. Use them as spacers, feet, cushions, protectors, vibration and shock absorbers.

Typical applications: glass and wood doors and drawers, small appliances, telephones, furniture, desktop and office equipment, housewares, advertising displays, wall protectors.

Bonding surface guide: aluminum, ceramic, formica, painted surfaces, glass, steel, polyethylene, polypropylene, polystyrene and rigid vinyl.

Rubber-based adhesive is stocked


and acrylic-based is available. (High surface energy plastics such as formica, acrylic and polycarbonates adhere best to acrylic-based adhesives. Low surface energy plastics such as polyethylene and polypropylene will adhere best to rubber-based adhesives.)

Call for a quote on special shapes and colours available.




Hemisphere

- U 2
- U 8
- U 15
- U 22
- U 25
- U 39
- U 40
- U 41
- U 42
- U 42SD



Tapered square

- U 3
- U 19
- U 29
- U 32



Square

- U 4
- U 7
- U 36



Circular Depression

- U 17
- U 18
- U 30



Tapered Conical

- U 37
- U 47
- U 57



Cylindrical

- U 1
- U 1SD
- U 5
- U 6
- U 11
- U 24
- U 34
- U 35
- U 410
- U 44
- U 72



Silent Closing Pyramid

- U 33

Continued



Feet and Bumpers

SELF-ADHESIVE CONTINUED

Part No.	Height	Width	Description	3M Equivalent	Pcs. per Pad
U 1	.14	.50 dia	Cylindrical	SJ 5012/5001/5312	200
U 1SD	.14	.50 dia	Soft Duro Cylindrical		200
U 2	.20	.44 dia	Hemisphere	SJ 5003/5303	242
U 3	.23	.50 sq	Tapered Square	SJ 5018	200
U 4	.38	.78 sq	Square		1
U 5	.06	.50 dia	Cylindrical		200
U 6	.25	.50 dia	Cylindrical		200
U 7	.10	.40 sq	Square	SJ 5007	242
U 8	.38	.70 dia	Hemisphere	SJ 5017	98
U 11	.40	.65 dia	Cylindrical		128
U 15	.31	.62 dia	Hemisphere	SJ 5027	128
U 17	.40	.88 dia	Circular depression	SJ 5009	72
U 18	.14	.50 dia	Circular depression		200
U 19	.30	.81 sq	Tapered square	SJ 5023	98
U 22	.21	.375 dia	Hemisphere		300
U 24	.12	.81 dia	Cylindrical		72
U 25	.079	.250 dia	Hemisphere		450
U 29	.25	.78 sq	Tapered Square		98
U 30	.60	1.81 dia	Circular depression	SJ 5532	1
U 32	.12	.50 sq	Tapered square	SJ 5008	200
U 33	.15	.50 sq	Special Tapered Sq.		200
U 34	.125	.375 dia	Cylindrical		300
U 35	.19	.37 dia	Cylindrical		200
U 36	.18	1.00 sq	Square		55
U 37	.56	.72 dia	Tapered conical		1 or 4
U 39	.08	.75 dia	Hemisphere		84
U 40	.06	.25 dia	Hemisphere		578
U 41	.09	.33 dia	Hemisphere	SJ 5302	450
U 410	.20	.78 dia	Cylindrical		84
U 42	.15	.38 dia	Hemisphere	SJ 5306	200
U 42SD	.15	.38 dia	Soft Duro Hemisphere		200
U 44	.16	.75 dia	Cylindrical		98
U 47	.75	.75 dia	Tapered conical		1 or 4
U 57	.886	.787 dia	Tapered conical		1 or 4
U 72	.100	1.230 dia	Cylindrical		32

Minimum order 1000.

Stock colours: Black or clear.

White, brown and gray available in carton quantity only.

Tolerance all dimensions: ± 0.020

Technical data: see page 76.

U 33 not recommended as weight bearing.

User should evaluate product suitability for a specific application under actual use conditions.