



Plastic Tube and Hose Fittings

ADAPTERS—MALE



Suggested advantages:

- No corrosion
- Lightweight
- Can often be used with fluids that attack metals
- Low cost
- Do not cut fingers
- Electrically non-conductive
- No galvanic reaction with metals
- Made of materials listed by FDA.

Other fittings not listed here are available. Can be run in other materials (eg. nylon 6-6HS, polypropylene) for a minimum of 10,000.

NOTES:

MPT—Male taper pipe thread
GHT—Garden hose thread

Temperature Ratings

HDPE: -55° to +90°C
Nylon: -40° to +100°C

ADAPTERS—FEMALE



Part No.		MPT	Tube ID	
Nylon 6	Black HDPE			
F 253	F 253 PE		5/32	
F 23	F 23 PE		3/16	
F 24	F 24 PE	1/8	1/4	
F 25	F 25 PE		5/16	
F 26	F 26 PE		3/8	
F 43	F 43 PE		3/16	
F 44	F 44 PE	1/4	1/4	
F 45	F 45 PE		5/16	
F 46	F 46 PE		3/8	
F 48	F 48 PE		1/2	
F 64	F 64 PE		1/4	
F 65	F 65 PE	3/8	5/16	
F 66	F 66 PE		3/8	
F 68	F 68 PE		1/2	
F 610	F 610 PE		5/8	
F 83	F 83 PE	1/2	3/16	
F 84	F 84 PE		1/4	
F 86	F 86 PE		3/8	
F 88	F 88 PE		1/2	
F 810	F 810 PE		5/8	
F 812	F 812 PE		3/4	
F 816	—		1	
F 124	F 124 PE		3/4	1/4
F 126	F 126 PE			3/8
F 128	F 128 PF			1/2
F 1210	F 1210 PE	5/8		
F 1212	F 1212 PE	3/4		
F 1216	—	1		
F G3	—	GHT	3/16	
F G4	—		1/4	
F G6	—		3/8	
F G8	—		1/2	
F G10	—		5/8	
F G12	—		3/4	
F 1612	F 1612 PE		1	3/4
F 1616	F 1616 PE	1		
A 1141	—	1-1/4	1	
A 114	—		1-1/4	
A 114112	—		1-1/2	
A 11234	—	1-1/2	3/4	
A 1121	—		1	
A 112114	—		1-1/4	
A 112	—		1-1/2	
A 200	—		2	2

Minimum order 50.