

This UL Type B flexible, non-metallic tubing resists corrosion, abrasion, oil, water, acid, metal shavings and rough environments. It is for use with nylon straight, snap-in or sweep connectors as well as steel and die cast connectors. Mounting brackets are also available. Resists abuse, pull and crushing.

Smooth inside for easier wire pulling; will not harm conductors. No hazardous sharp edges or burrs. Quick installation. Suitable for indoor/outdoor use. Manufactured of flexible PVC.



Part No.	Trade Size (fraction)	Trade Size (In)	Trade Size (mm)	A Outside Diameter (In)	A Outside Diameter (mm)	B Inside Diameter (In)	B Inside Diameter (mm)
HF1-3/8	3/8	0.375	9.53	0.700	17.78	0.494	12.55
HF1-1/2	1/2	0.500	12.70	0.830	21.08	0.632	16.05
HF1-3/4	3/4	0.750	19.05	1.040	26.42	0.830	21.08
HF1-1	1	1.000	25.40	1.303	33.10	1.054	26.77
HF1-1-1/4	1-1/4	1.250	31.75	1.645	41.78	1.395	35.43
HF1-1-1/2	1-1/2	1.500	38.10	1.883	47.83	1.588	40.34
HF1-2	2	2.000	50.80	2.358	59.89	2.033	51.64

Standard colour: Gray.

**Countless Possibilities, Millions Of Solutions**  
**(416) 242-6811**