

## Straight


All nylon construction resists salt water, weak acids, gasoline, alcohol, oil, grease & common solvents. No disassembly required. Just push the conduit/tubing onto the ferrule, then tighten the domed sealing nut. This completed assembly can then be secured in the chassis by the locknut (or first secure the connector into an NPT threaded hole). No threading of the conduit or tubing is required, eliminating the chance of cutting the conduit and creating leak paths.

Complete connector is reusable.

Use of a sealing washer may be needed for wet locations.

Suitable for indoor/outdoor use, for original equipment manufacturers or field installers.

Black connectors provided with nylon locknut, packed separately. Gray connectors provided with assembled o-ring and metal locknuts.



Part No.	Fits Conduit Trade Size (fraction)	Fits Conduit Trade Size (In)	Fits Conduit Trade Size (mm)	A Clearance Hole (In)	A Clearance Hole (mm)	B Max OA Length (In)	B Max OA Length (mm)	C Thread Length (In)	C Thread Length (mm)	D Wrenching Nut Thickness (In)	D Wrenching Nut Thickness (mm)	E Wrenching Flats (In)	E Wrenching Flats (mm)	Sealing Washer
HFC3/8-BL	3/8	0.375	9.53	0.875	22.23	1.330	33.78	0.625	15.88	0.250	6.35	1.300	33.02	SW1/2
HFC1/2-BL	1/2	0.500	12.70	0.875	22.23	1.330	33.78	0.625	15.88	0.250	6.35	1.300	33.02	SW1/2
HFC3/4-BL	3/4	0.750	19.05	1.109	28.17	1.410	35.81	0.625	15.88	0.250	6.35	1.520	38.61	SW3/4
HFC1-BL	1	1.000	25.40	1.375	34.93	1.470	37.34	0.781	19.84	0.250	6.35	1.875	47.63	SW1
HFC1-1/4-BL*	1-1/4	1.250	31.75	1.688	42.88	2.120	53.85	0.715	18.16	0.250	6.35	--	--	--
HFC1-1/2-BL*	1-1/2	1.500	38.10	1.938	49.23	2.420	61.47	0.680	17.27	0.250	6.35	--	--	--
HFC2-BL*	2	2.000	50.80	2.375	60.33	2.490	63.25	0.680	17.27	0.250	6.35	--	--	--

Standard colour: Black. Also available in Gray. Please substitute GRAY for BL when ordering.

\*Sizes larger than 1" are manufactured in PVC.

Countless Possibilities, Millions Of Solutions  
(416) 242-6811