


Nail-In Cable Clips

These nail-in cable clips are used to safely install cable TV, fibre optics, computer networks, telephone and other communication systems, hydraulic and pneumatic systems. They are moulded in tough, ultra-violet resistant, electrically insulating, high density polyethylene. The main stress areas of the clip have reinforcing ribs designed into the part to strengthen and absorb impact. The contact edges are radiused to protect damage to cable or tubing.

Pre-assembled with heat-treated, galvanized steel nails, ready for use in masonry, wood, stucco or plaster. Easily and efficiently installed.





Compno	STKNO	ATRBUT	Value	Unit Measure
D	NICC-40	W (in)	0.157	In
D	NICC-40	W (mm)	3.99	mm
D	NICC-40	H (in)	0.260	In
D	NICC-40	H (mm)	6.60	mm
D	NICC-40	H1 (in)	0.165	In
D	NICC-40	H1 (mm)	4.19	mm
D	NICC-50	W (in)	0.100	In
D	NICC-50	W (mm)	2.54	mm
D	NICC-50	H (in)	0.299	In
D	NICC-50	H (mm)	7.59	mm
D	NICC-50	H1 (in)	0.209	In
D	NICC-50	H1 (mm)	5.31	mm
D	NICC-70	W (in)	0.236	ln
D	NICC-70	W (mm)	5.99	mm
D	NICC-70	H (in)	0.354	In

Countless Possibilities, Millions Of Solutions

(416) 242-6811

D	NICC-70	H (mm)	8.99	mm
D	NICC-70	H1 (in)	0.260	In
D	NICC-70	H1 (mm)	6.60	mm
D	NICC-80	W (in)	0.315	In
D	NICC-80	W (mm)	8.00	mm
D	NICC-80	H (in)	0.453	In
D	NICC-80	H (mm)	11.51	mm
D	NICC-80	H1 (in)	0.339	In
D	NICC-80	H1 (mm)	8.61	mm
D	NICC-40	Material	HDPE	
D	NICC-50	Material	HDPE	
D	NICC-70	Material	HDPE	
D	NICC-80	Material	HDPE	
D	NICC-40	Colour	Black	
D	NICC-50	Colour	Black	
D	NICC-70	Colour	Black	
D	NICC-80	Colour	Black	

Standard colour: Black or white (add suffix W when ordering).

Countless Possibilities, Millions Of Solutions (416) 242-6811