

Value-Line – Screw Mountable


Care and Feeding of Nylon Cable Ties (and other nylon parts)

Here are the two most common problems that come up for customers using nylon cable ties. You will be pleased to know that these two problems can almost always be corrected without having to return the ties.

Brittle ties: When bags of cable ties are sealed at the factory, a few drops of water are added to keep the ties from drying out. Due to the nature of nylon, it is recommended that you not open sealed bags until you need to use the ties and that you re-seal them when not in use. When storing bags of cable ties, keep them in an area where they won't be affected by heat and dry atmospheres. These suggestions hold true for most nylon parts. If you find you have a bunch of ties that have become brittle, put them in a plastic bag with 1/4 teaspoon of water and seal the bag. (If you put in more water than that, the ties will get rubbery and you'll have to let them dry out again!) Leave them overnight. Chances are the next day the ties will be fine again. If, however, you still find the ties are brittle, please call us.

Locking mechanism “breaking out”:

There are usually two reasons for this. The first is that the tension setting on the tightening tool/tie gun being used may be set too high and needs to be adjusted. The other reason is that the ties are being incorrectly tightened by hand. When inserting the tail into the locking mechanism, it should be pulled through in a straight line. It should not be pulled and bent back in the same manner one inserts a belt into a buckle.



Part No.	Approximate Length (fraction)	Approximate Length (In)	Approximate Length (mm)	Maximum Bundle Dia. (fraction)	Maximum Bundle Dia. (In)	Maximum Bundle Dia. (mm)	Minimum Tensile Strength	Suggested Mounting Screw Size (fraction)	Suggested Mounting Screw Size (In)	Suggested Mounting Screw Size (mm)	Minimum Order Qty.
Standard Duty											
VMNT5-30	6	6.000	152.40	1-1/4	1.250	31.75	30	8	8.000	203.20	1000
VMNT7-50	7-1/2	7.500	190.50	1-3/4	1.750	44.45	50	10	10.000	254.00	1000
VMNT11-50	11	11.000	279.40	3	3.000	76.20	50	10	10.000	254.00	1000
VMNT14-50	14-1/2	14.500	368.30	4	4.000	101.60	50	10	10.000	254.00	500
Heavy Duty											
VMNT14-120	14-1/2	14.500	368.30	4	4.000	101.60	120	1/4	0.250	6.35	100

UV Black available at an additional charge.

Countless Possibilities, Millions Of Solutions
(416) 242-6811