




Used with self-threading metal screws, these snap-in nuts expand and securely lock screws and assembled parts in place, connecting thin-gauge materials and eliminating cross-threading. They are corrosion and vibration resistant. Design variation is available.



Part No.	Square hole Size (in)	Square hole Size (mm)	Panel Thickness (in)	Panel Thickness (mm)	Screw Size	H Head size (in)	H Head Size (mm)	T Head Height (in)	T Head Height (mm)	L Length (in)	L Length (mm)
<b>Square Head</b>											
XN-1S	.275-.290	6.99-7.37	.031-.125	0.79-3.18	8 or 10	0.375	9.53	0.031	0.79	0.320	8.13
XN-2S	.275-.290	6.99-7.37	.031-.125	0.79-3.18	8 or 10	0.375	9.53	0.062	1.57	0.320	8.13
XN-4S	.275-.290	6.99-7.37	.031-.125	0.79-3.18	8 or 10	0.375	9.53	0.125	3.18	0.320	8.13
XN-8S	.275-.290	6.99-7.37	.031-.125	0.79-3.18	8 or 10	0.375	9.53	0.250	6.35	0.320	8.13
XN-10S	.250-.255	6.35-6.48	.110-.125	2.79-3.18	6	0.375	9.53	0.031	0.79	0.265	6.73
XN-1014	.250-.270	6.35-6.86	.062-.155	1.57-3.94	6	0.375	9.53	0.032	0.81	0.312	7.92
XN-22S	.350-.355	8.89-9.02	.218-.230	5.54-5.84	8 or 10	0.475	12.07	0.062	1.57	0.421	10.69
XN-30S	.370-.375	9.40-9.53	.031-.100	0.79-2.54	12	0.620	15.75	0.080	2.03	0.275	6.99
<b>Double Split Square Head</b>											
XN-10DS	.377-.382	9.58-9.70	.125-.130	3.18-3.30	10	0.609	15.47	0.082	2.08	0.308	7.82
XN-19DS	.305-.310	7.75-7.87	.125-.135	3.18-3.43	8	0.437	11.10	0.062	1.57	0.281	7.14
XN-1025	.250-.250	6.35-6.35	.093-.275	2.36-6.99	8	0.375	9.53	0.047	1.19	0.42	10.67
XN-1128	.330-.330	8.38-8.38	.031-.125	0.79-3.18	8	0.505	12.83	0.032	0.81	0.275	6.99
<b>Round Head</b>											
XN-4R	.271-.290	6.88-7.37	.031-.125	0.79-3.18	8-10	0.500	12.70	0.125	3.18	0.320	8.13
XN-8R	.275-.290	6.99-7.37	.031-.125	0.79-3.18	8-10	0.500	12.70	0.250	6.35	0.320	8.13
XN-38R	.275-.290	6.99-7.37	.031-.156	0.79-3.96	8	0.500	12.70	0.375	9.53	0.320	8.13
XN-72R	.275-.290	6.99-7.37	.031-.156	0.79-3.96	8-10	0.500	12.70	0.708	17.98	0.315	8.00
XN-220R	.425-.429	10.80-10.90	.031-.110	0.79-2.79	5/16	0.740	18.80	0.190	4.83	0.312	7.92


**Countless Possibilities, Millions Of Solutions**  
**(416) 242-6811**

Three Legged Square Head (Fits Round Hole)											
XN-3300	.300-.300	7.62-7.62	.031-.135	0.79-3.43	6	0.485	12.32	0.055	1.40	0.265	6.73

Minimum order 1000

### Closed Bottom

Provides the same advantage as our standard expansion nuts but with various head thicknesses and a closed bottom. This part can also be manufactured in Supertough Nylon to accommodate a #10 screw.



Part No.	A Hole Size (in)	A Hole Size (mm)	Panel Thickness (in)	Panel Thickness (mm)	Screw Size	B Head Dimension (in)	B Head Dimension (mm)	C Head Thickness (in)	C Head Thickness (mm)	Length (in)	Length (mm)
XN-651	0.281	7.14	.020-.140	0.51-3.56	6-8	0.375	9.53	0.620	15.75	0.430	10.92
XN-718	0.281	7.14	.020-.140	0.51-3.56	6-8	0.375	9.53	0.187	4.75	0.430	10.92
XN-773	0.281	7.14	.020-.140	0.51-3.56	6-8	0.375	9.53	0.500	12.70	0.430	10.92
XN-811	0.281	7.14	.020-.140	0.51-3.56	6-8	0.375	9.53	0.312	7.92	0.430	10.92
XN-1241	0.281	7.14	.020-.140	0.51-3.56	6-8	0.375	9.53	0.125	3.18	0.430	10.92
XN-1315	0.281	7.14	.010-.140	0.51-3.56	6-8	0.375	9.53	0.500	12.70	0.430	10.92

Minimum order 1000

**Countless Possibilities, Millions Of Solutions**  
**(416) 242-6811**

62 Densley Avenue, Toronto, Ontario Canada M6M 5E1

[cordscanada.com](http://cordscanada.com)