


Metric Nylon Flat Washers

Seal, insulate, absorb shock and vibration. They prevent galling and marring, and may also be used as spacers, guides, bearings, bushings, etc.

Other sizes can be tooled for moulding or stamping in any plastic. Request a quotation, specifying size, tolerance and quantity.



Part No.	I.D.		O.D.		Thickness		Material	Colour
	mm	in	mm	in	mm	in		
MFW 2	2.15	0.085	5.00	0.197	0.80	0.031	Nylon	Natural
MFW 2.5	2.65	0.104	5.60	0.220	0.80	0.031	Nylon	Natural
MFW 3	3.20	0.125	8.00	0.315	0.80	0.031	Nylon	Natural
MFW 3.5	3.70	0.146	8.00	0.315	0.80	0.031	Nylon	Natural
MFW 4	4.30	0.169	9.00	0.354	0.80	0.031	Nylon	Natural
MFW 5	5.30	0.208	11.00	0.433	1.00	0.040	Nylon	Natural
MFW 6	6.40	0.252	12.00	0.472	1.50	0.060	Nylon	Natural
MFW 8	8.40	0.330	18.00	0.709	2.00	0.080	Nylon	Natural
MFW 10	10.50	0.413	22.00	0.866	2.50	0.098	Nylon	Natural

Minimum order 1000.

Countless Possibilities, Millions Of Solutions
(416) 242-6811