

Open/Closed Bushings

A black nylon bushing for side entry and encirclement of preassembled harnesses, capillary tubes or other units that have sections larger than the bushing's ID. Can also be assembled into holes that already contain cable or tubing. Fingertip pressure snaps the bushing into the mounting hole, forming a complete circle and insulation barrier against the raw edge of the chassis hole.



Part No.	Mounting Hole		A		B		C		Max. Chassis		Minimum Order Quantity
	Diameter	mm	Inside Diameter	mm	Head Diameter	mm	Overall Height	mm	Thickness	mm	
OCB375	0.375	9.53	0.265	6.73	0.421	10.69	0.390	9.91	0.125	3.18	1,000
OCB437	0.437	11.10	0.312	7.92	0.500	12.70	0.406	10.31	0.125	3.18	1,000
OCB500	0.500	12.70	0.312	7.92	0.562	14.27	0.406	10.31	0.125	3.18	1,000
OCB562	0.562	14.27	0.390	9.91	0.640	16.26	0.406	10.31	0.125	3.18	1,000
OCB625	0.625	15.88	0.453	11.51	0.687	17.45	0.406	10.31	0.125	3.18	1,000
OCB750	0.750	19.05	0.546	13.87	0.796	20.22	0.406	10.31	0.125	3.18	1,000
OCB875	0.875	22.23	0.671	17.04	0.921	23.39	0.406	10.31	0.125	3.18	1,000
OCB1000	1.000	25.40	0.812	20.62	1.047	26.59	0.406	10.31	0.125	3.18	500
OCB1093	1.093	27.76	0.875	22.23	1.156	29.36	0.406	10.31	0.125	3.18	1,000
OCB1250	1.250	31.75	1.046	26.57	1.343	34.11	0.406	10.31	0.125	3.18	500
OCB1375	1.375	34.93	1.171	29.74	1.468	37.29	0.406	10.31	0.125	3.18	500
OCB1500	1.500	38.10	1.250	31.75	1.578	40.08	0.421	10.69	0.125	3.18	500

Standard colour: Black

White and other colours available at premium charge if quantities are sufficient.

Countless Possibilities, Millions Of Solutions

(416) 242-6811