



Push Mount Clamps

Can be used in a wide variety of environmental conditions and on any surface up to .080" thick. Just snap into a .250" hole and the push-mount will hold a 25 lb. continuous load and a 50 lb. impact load. Unique lock/release feature operates easily and locks securely. Available in 94V-0 polypropylene for an additional charge. Add-V0 suffix to part number when ordering. For use with chassis and panels .020" to .080" thick.



Release tab provides easy opening without forcing.

Barbed locking element ensures reliable retention.

Quick lock/release allows fast lock-up and easy access to wire bundle.

Unique design of push mount permits fast installation and provides high pull-out resistance.

Part No.	A (In)	A (mm)	B (In)	B (mm)	C (In)	C (mm)	D (In)	D (mm)	E (In)	E (mm)	F (In)	F (mm)	Max Bundle Dia. (fraction)	Max Bundle Dia. (In)	Max Bundle Dia. (mm)
029-0188	0.550	13.97	1.000	25.40	0.390	9.91	0.380	9.65	0.200	5.08	0.300	7.62	3/16	0.188	4.76
029-0250	0.580	14.73	1.000	25.40	0.440	11.18	0.410	10.41	0.200	5.08	0.300	7.62	1/4	0.250	6.35
029-0375	0.650	16.51	1.000	25.40	0.530	13.46	0.500	12.70	0.200	5.08	0.300	7.62	3/8	0.375	9.53
029-0500	0.770	19.56	1.190	30.23	0.720	18.29	0.600	15.24	0.200	5.08	0.300	7.62	1/2	0.500	12.70
029-0750	0.880	22.35	1.380	35.05	0.970	24.64	0.670	17.02	0.200	5.08	0.300	7.62	3/4	0.750	19.05
029-1000	1.370	34.80	1.880	47.75	1.300	33.02	1.000	25.40	0.200	5.08	0.300	7.62	1	1.000	25.40

Countless Possibilities, Millions Of Solutions
(416) 242-6811