




Snap Bushings

These nylon bushings convert raw-edged holes to smooth, neat, insulated ones. Special locking “fingers” allow the bushings to snap into holes with fingertip pressure. Mechanically protect, insulate, and isolate telecommunications and electrical cables, tubing, hose, rope and utility lines.

SB312-3, SB375-4 and SB437-4 are also available as brass-coloured parts for lamp and lighting applications.



Part No.	Mounting Hole Diameter	A Inside Diameter	B Head Diameter	C Overall Height	Max. Chassis Thickness	Minimum Order Quantity
SB250-040*	0.25	0.125	0.312	0.312	0.04	1,000
SB250-2*	0.25	0.125	0.312	0.312	0.062	1,000
SB312-3*	0.312	0.187	0.375	0.312	0.062	1,000
SB375-3	0.375	0.187	0.468	0.406	0.125	1,000
SB375-4	0.375	0.25	0.468	0.406	0.125	1,000
SB375-281*	0.375	0.281	0.468	0.406	0.172	1,000
SB437-4	0.437	0.27	0.531	0.406	0.125	1,000
SB437-5	0.437	0.312	0.531	0.406	0.125	1,000
SB437-243	0.437	.243 +.015,-.000	0.531	0.406	0.125	1,000
SB500-4	0.5	0.25	0.578	0.406	0.125	1,000
SB500-5	0.5	0.312	0.578	0.406	0.125	1,000
SB500-6	0.5	0.391	0.578	0.406	0.125	1,000
SB562-5	0.562	0.312	0.656	0.406	0.125	1,000
SB562-6	0.562	0.391	0.656	0.406	0.125	1,000
SB562-7	0.562	0.437	0.656	0.406	0.125	1,000
SB625-4	0.625	0.25	0.718	0.406	0.125	1,000
SB625-7	0.625	0.437	0.718	0.406	0.125	1,000

**Countless Possibilities, Millions Of Solutions
(416) 242-6811**

SB625-8	0.625	0.5	0.718	0.406	0.125	1,000
SB625-500*	0.625	.500 +.015,-.000	0.703	0.531	0.28	1,000
SB687-8	0.687	0.5	0.781	0.406	0.125	1,000
SB687-9	0.687	0.562	0.781	0.406	0.125	1,000
SB750-6	0.75	0.391	0.843	0.406	0.125	1,000
SB750-8	0.75	0.5	0.843	0.406	0.125	1,000
SB750-9	0.75	0.562	0.843	0.406	0.125	1,000
SB750-10	0.75	0.609	0.843	0.406	0.125	1,000
SB750-625*	0.75	.625 +.015 -.000	0.828	0.531	0.25	1,000
SB812-9	0.812	0.562	0.89	0.406	0.125	1,000
SB812-10	0.812	0.625	0.89	0.406	0.125	1,000
SB875-6	0.875	0.375	0.953	0.453	0.125	1,000
SB875-7	0.875	0.437	0.953	0.453	0.125	1,000
SB875-8	0.875	0.5	0.953	0.453	0.125	1,000
SB875-9	0.875	0.562	0.953	0.453	0.125	1,000
SB875-10	0.875	0.625	0.953	0.453	0.125	1,000
SB875-11	0.875	0.687	0.953	0.453	0.125	1,000
SB1000-12	1	0.766	1.125	0.453	0.125	500
SB1093-13	1.093-1.125	0.812	1.218	0.453	0.125	500
SB1093-14	1.093-1.125	0.875	1.218	0.453	0.125	500
SB1093-15	1.093-1.125	0.937	1.218	0.453	0.125	500
SB1187-15	1.187	0.937	1.312	0.453	0.125	500
SB1250-15	1.25	0.937	1.359	0.453	0.125	500
SB1250-16	1.25	1	1.31	0.453	0.125	500
SB1375-14	1.375	0.875	1.468	0.453	0.125	500
SB1375-16	1.375	1	1.468	0.453	0.125	500
SB1500-17	1.5	1.062	1.609	0.453	0.125	500
SB1500-18	1.5	1.125	1.609	0.453	0.125	500
SB1500-21	1.5	1.312	1.609	0.453	0.125	500
SB1750-22	1.75	1.375	1.875	0.453	0.125	300
SB2000-26	2	1.64	2.125	0.453	0.125	300
SB2000-28	2	1.75	2.125	0.453	0.125	300
SB2093-29	2.093	1.813	2.35	0.72	0.25	300
SB2.25-29	2.25	1.86	2.48	0.72	0.25	100
SB2.5-31	2.5	1.97	2.66	0.72	0.25	100
SB3.0-39	3	2.47	3.16	0.72	0.25	100
SB3375-45	3.375	2.812	3.66	0.72	0.25	100

**Countless Possibilities, Millions Of Solutions
(416) 242-6811**

SB3.5-47	3.5	2.94	3.66	0.72	0.25	100
SB4.0-55	4	3.48	4.17	0.72	0.25	100
SB5.0-75	5	4.375	5.219	0.74	0.25	150
SB6.0-86	6	5.375	6.219	0.74	0.25	130

Standard colour: Black. White and other colours available at premium charge if quantities are sufficient.

*Depicts single chassis design.

**Countless Possibilities, Millions Of Solutions
(416) 242-6811**

62 Densley Avenue, Toronto, Ontario Canada M6M 5E1

cordscanada.com