



Straight-Thru Liquid Tight Fitting

All nylon construction with BUNA-N compression gland resists salt water, weak acids, gasoline, alcohol, oil, grease and common solvents. Fittings install in either clearance or threaded holes. Acme threads prevent skipping and speed installation. The domed sealing nut resists snags and sheds contaminants. An internal ratchet provides self-locking against vibration. Working temperatures: -22°F (-30°C) to 212°F (100°C). For short periods to 302°F (150°C). Protection class IP 68 per DIN 40050 up to 70 psi (5 bar) water pressure. Available in metric.



Installation Note: For optimum liquid tightness, use fitting with the smallest maximum diameter that will still fit your application.

PG Hubs For Flexible Cords (Locknuts Included)

Part No.		Cable Dia. Range Min.-Max. (In)	Cable Dia. Range Min.-Max. (mm)	Thread Type & Size	A Clearance Hole (In)	A Clearance Hole (mm)	B Max. O.A. Length (In)	B Max. O.A. Length (mm)	C Thread Length (In)	C Thread Length (mm)	D Wrenching Nut Thick. (In)	D Wrenching Nut Thick. (mm)	E Wrenching Flats (In)	E Wrenching Flats (mm)
Black	Grey													
3207	3208	.114-.250	2.90-6.35	PG-7	0.492	12.50	1.170	29.72	0.330	8.38	0.200	5.08	0.590	14.99
3444	3445	.064-.210	1.63-5.33	PG-7	0.492	12.50	1.170	29.72	0.330	8.38	0.200	5.08	0.590	14.99
3210	3211	.181-.312	4.60-7.92	PG-9	0.599	15.21	1.300	33.02	0.340	8.64	0.200	5.08	0.750	19.05
3446	3447	.069-.187	1.75-4.75	PG-9	0.599	15.21	1.300	33.02	0.340	8.64	0.200	5.08	0.750	19.05
3213	3214	.230-.395	5.84-10.03	PG-11	0.733	18.62	1.460	37.08	0.390	9.91	0.200	5.08	0.860	21.84
3448	3449	.069-.250	1.75-6.35	PG-11	0.733	18.62	1.460	37.08	0.390	9.91	0.200	5.08	0.860	21.84
3216	3217	.170-.450	4.32-11.43	PG-13.5	0.804	20.42	1.530	38.86	0.410	10.41	0.200	5.08	0.950	24.13
3219	3220	.230-.530	5.84-13.46	PG-16	0.886	22.50	1.660	42.16	0.450	11.43	0.230	5.84	1.050	26.67
3222	3223	.450-.705	11.43-17.91	PG-21	1.115	28.32	1.870	47.50	0.520	13.21	0.230	5.84	1.300	33.02
3454	3455	.250-.490	6.35-12.45	PG-21	1.115	28.32	1.870	47.50	0.520	13.21	0.230	5.84	1.300	33.02
3225	3226	.590-.990	14.99-25.15	PG-29	1.470	37.34	2.230	56.64	0.590	14.99	0.280	7.11	1.660	42.16
M3204	M3205	.875-1.260	22.23-32.00	PG-36	1.850	46.99	2.520	64.01	0.510	12.95	0.320	8.13	2.090	53.09
M3206	M3203	.787-1.020	19.99-25.91	PG-36	1.850	46.99	2.520	64.01	0.510	12.95	0.320	8.13	2.090	53.09
3212	--	1.260-1.496	32.00-37.99	PG-42	2.125	53.98	2.640	67.06	0.510	12.95	0.360	9.14	2.360	59.94
3218	--	.984-1.220	24.99-30.99	PG-42	2.125	53.98	2.640	67.06	0.510	12.95	0.360	9.14	2.360	59.94
3281	--	1.457-1.732	37.00-44.00	PG-48	2.335	59.31	2.720	69.09	0.550	13.97	0.360	9.14	2.560	65.02
3283	--	1.142-1.378	28.96-35.00	PG-48	2.335	59.31	2.720	69.09	0.550	13.97	0.360	9.14	2.560	65.02

Countless Possibilities, Millions Of Solutions
(416) 242-6811