


Heyco® Nylon Corrugated Conduit/Tubing Mounting Clips with Integral Closure

Snap it; Secure it; Forget it!

Conduit/Tubing Management

Features & Benefits

- For mounting Heyco Nylon Corrugated Conduit or Tubing securely into place, vertically or horizontally.
- Low profile design for space savings and pleasing appearance.
- Only fingertip pressure is required to snap conduit or tubing into bracket.
- Can be easily opened for temporary access/removal and closed again to secure conduit.
- Suitable for use with both fine and/or coarse pitch conduit/tubing.
- Suitable for use by original equipment manufacturers.
- Resist salt water, weak acids, gasoline, alcohol, oil, grease, and common solvents. (This feature is not assessed by UL certification or testing.)
- Recommended distance between brackets at intervals not greater than 3 feet (914 mm) as required by Article 351-27 of 1996 NEC.
- Use one standard #10 (4-5M) screw for attaching bracket to panel or chassis (screw not included).



Specifications

FITS TRADE SIZE	PART NO. Black	DESCRIPTION	PART DIMENSIONS							
			A Mounting Hole Dia.		B Width		C Max O.A. Height		D Max.O.A. Thickness	
			in.	mm.	in.	mm.	in.	mm.	in.	mm.
13 mm	F8902A	CONDUIT CLIP A 13MM FCL13/BL	.21	5,2	.91	23,2	.92	23,3	.46	11,6
16 mm	F8904A	CONDUIT CLIP A 16MM FCL16/BL	.20	5,1	1.05	26,7	1.06	26,9	.54	13,7
21 mm	F8906A	CONDUIT CLIP A 21MM FCL21/BL	.24	6,1	1.33	33,8	1.37	34,9	.69	17,5
28 mm	F8908A	CONDUIT CLIP A 28MM FCL28/BL	.24	6,1	1.72	43,8	1.75	43,7	.81	20,7
34 mm	F8910A	CONDUIT CLIP A 34MM FCL34/BL	.24	6,1	2.08	52,8	2.03	51,6	.91	23,2
42 mm	F8912A	CONDUIT CLIP A 42MM FCL42/BL	.25	6,2	2.54	64,5	2.46	62,5	1.06	27,0

Material Quick Specs:

Material : Nylon 6/6 Standard colour: Black

Flammability Rating: 94V-2 and Low Fire Hazard Including Low Smoke, Low Toxicity as well as Halogen, Sulphur, and Phosphorus Free

Temperature Range: -40°F (-40°C) to 185°F (85°C)

Visit our blog for more information.